



MECHANIC'S GLOVES PADDED PALM

MODEL NO: **MG796L.V3 & MG796XL.V3**



Thank you for purchasing a Sealey product. Manufactured to a high standard, this product will, if used according to these instructions, and properly maintained, give you years of trouble free performance.



REFER TO INSTRUCTIONS

IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS & CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. KEEP THESE INSTRUCTIONS SAFE FOR FUTURE USE.

1. INTRODUCTION


Close fitting gloves suitable for professional workshop use. Palm is padded with cushion points giving added protection against vibration, ideal for use with air or electric power tools. Extra protection between the index finger and thumb to protect the hand. Hook-and-loop wrist strap. Large/Extra-Large Sizes.

The gloves shall not be worn when there is a risk of entanglement by moving parts of machines.

2. SAFETY

- ✓ Users should be warned that gloves should not be worn when there is a risk of entanglement by moving parts of machines.
- ✓ This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.
- ✓ The protection against risks or hazards which are not mentioned in this document is not warranted.
- ✓ The levels of performance mentioned are only valid for the palm of the glove.
- ✓ These levels of performance are obtained from the tests done according to the conditions defined by the applicable standards.
- ✓ This glove shall not be in contact with fire.
- ✓ Before use, the glove shall be visually controlled. In case of deterioration the gloves must be scrapped (abrasion, cut, tear, ...).
- ✓ For gloves with two or more layers of material, the performance levels are warranted only for the whole glove.
- ✓ For gloves with two or more layers the overall classification does not necessarily reflect the performance of the outermost layer.
- ✓ Select gloves based on the task, conditions, duration of use, and hazards.
- ✓ Ensure gloves are comfortable and fit well, encouraging consistent wear.
- ✓ Replace gloves when they show visible signs of wear, damage, or degradation. There is no fixed time limit for glove wear; instead, the focus is on condition-based replacement.
- ✓ Retain original packaging for transportation purposes.

3. APPLICABLE STANDARDS

Mechanical Hazard EN 388 : 2016  2122X	Abrasion Resistance	2	(on 4 maxi)	'X' indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.
	Blade Cut Resistance	1	(on 5 maxi)	
	Tear Resistance	2	(on 2 maxi)	
	Puncture Resistance	2	(on 4 maxi)	
	Cut Resistance Method (EN ISO 13997)	X	(A to F)	
	Impact Protection	-		

4. MAINTENANCE

4.1. STORAGE

- ✓ Store the gloves in normal temperature and humidity conditions.
- ✓ Store the gloves in clean, covered and ventilated premises.

4.2. CLEANING

- ✗ Cleaning is not recommended.

4.3. MAINTENANCE

- ✓ The gloves should be inspected before each use, and replaced if damaged.
- ✓ When stored in appropriate conditions, performance of this product will not be significantly reduced.

This document has been drawn up according to Regulation (EU) 2016/425 as amended to apply to GB for Personal Protective Equipment. The declaration of conformity can be accessed at www.sealey.co.uk.



ENVIRONMENT PROTECTION

Recycle unwanted materials instead of disposing of them as waste. All tools, accessories and packaging should be sorted, taken to a recycling centre and disposed of in a manner which is compatible with the environment. When the product becomes completely unserviceable and requires disposal, drain any fluids (if applicable) into approved containers and dispose of the product and fluids according to local regulations.



REGISTER YOUR
PURCHASE HERE

Note: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice.

Important: No Liability is accepted for incorrect use of this product.

Warranty: Guarantee is 12 months from purchase date, proof of which is required for any claim.

Jack Sealey Ltd t/a Sealey Group, Kempson Way, Suffolk Business Park, Bury St Edmunds, Suffolk, IP32 7AR UK
Jack Sealey (EU) Ltd t/a Sealey Group, Farney Street, Carrickmacross, Co. Monaghan, A81 PK68 Ireland
Tel: 01284 757500 • **Email:** sales@sealey.co.uk • **Web:** www.sealey.co.uk